

## CLAIMS

### CLAIMS

1. A method for three-dimensional printing of a three-dimensional model,  
5       said method comprising:  
              selectively dispensing a first interface material and a second  
              interface material from a printing head, said first interface material and  
              said second interface material being different;  
              each of said first interface material and said second  
10       interface material comprising photopolymer materials.
2. A method according to claim 1, wherein one of said first interface material  
      and second interface material includes reactive acrylates and is curable by  
      the application of radiation.
3. A method according to claim 1, comprising ejecting said first interface  
15       material and said second interface material in a given layer in different mix  
      formulations to form a specified type of material.
4. A method according to claim 1, comprising curing said first and second  
      interface materials using radiation, said radiation being any one of a group  
      including ultra-violet radiation, infra-red radiation and E-beam.
- 20       5. A method according to claim 3, wherein said mix formulation of first  
          interface material and second interface material forms a model layer.
6. A method according to claim 3, wherein said mix formulation of first  
      interface material and second interface material forms a support layer.

7. A method according to claim 3, wherein said mix formulation of first interface material and second interface material forms a release layer.
8. A system for three-dimensional printing of a three-dimensional model, said system comprising:
- 5           a printing head for selectively dispensing a first interface material and a second interface material, said first interface material and said second interface material being different;
- each of said first interface material and said second interface material comprising photopolymer materials; and
- 10          a source of radiation for curing of at least one of said interface materials.
9. A system according to claim 8, wherein one of said first interface material and second interface material includes reactive acrylates.
10. A system according to claim 8, wherein said printing head is an ink-jet printing head.
- 15
11. A system according to claim 8, wherein said second interface material is curable.
12. A system according to claim 8, wherein said first interface material and said second interface material are ejected in a given layer in different mix formulations to form different types of materials.
- 20
13. A system according to claim 8, wherein said radiation is any one of a group including ultra-violet radiation, infra-red radiation and E-beam.

14. A system according to claim 12, wherein said mix formulation of first interface material and second interface material forms a model layer.

15. A system according to claim 12, wherein said mix formulation of first interface material and second interface material forms a support layer.

5 16. A system according to claim 12, wherein said mix formulation of first interface material and second interface material forms a release layer.